

DraftSeal®

Weathersealing Specialists Since 1960



THRESHOLDS & WEATHERSEALS FOR COMMERCIAL DOOR APPLICATIONS

REFER TO DRAFTSEAL RESIDENTIAL CATALOGUE FOR PRE-HUNG DOOR COMPONENTS: SILLS, SWEEPS, WEATHERSEALS & ASTRAGALS

DraftSeal® Full Line Commercial Catalogue • Revision (5) December 2021

PRINTED CATALOGUE MAY NOT BE UP TO DATE, ALWAYS REFER TO PRODUCT WEBSITE FOR MOST UP TO DATE CONTENT

ABOUT A.K. DRAFT SEAL LTD. & KRISTRACK

Tomorrow's Innovative Solutions for Today's Doors & Windows



Weathersealing Specialists Since 1960 - Weatherstripping, Thresholds, Sweeps & Astragals

Draft Seal Co. was founded in 1960 by Anton Kamensek then incorporated in 1973 as **A.K. Draft Seal Ltd.** During the 1990's we became known by our trademark name **DraftSeal®**, the largest manufacturer of weatherstrip products in Western Canada. After his retirement in the early nineties, his son, Chris, who had been with the company since 1973, purchased **DraftSeal®** and started the **Kristrack®** division. The year 2010 marked the 50th year in business for **DraftSeal®** as a manufacturer and supplier of weathersealing and door sill products for commercial and residential applications.

In 2013 we introduced our new DS1 Storm - Sill System to comply with the new building code that requires exterior door sill systems to be tested for air, water and structural. We will be introducing our new DSF1 Accordion Screen, which is integrated with our DS1 Storm - Sill System. Our manufacturing centre in British Columbia, Canada, produces a line of weatherstrip and sill products for the pre-hung door industry as well as a do-it-yourself line of residential weatherstripping for the consumer market.



Interior Track And Hardware For Sliding, Bifold And Pocket Doors

KrisTrack® Manufacturing Ltd., was formed in 1991 to compliment the **DraftSeal®** line of weathersealing and door sill products. **KrisTrack®** manufactures and supplies sliding and bifold door track with accompanying hardware and accessories; applications include residential, commercial and industrial. The year 2016 marked the 25th year in business for **KrisTrack**. Our manufacturing centre in British Columbia, Canada, also produces a line of specialty pocket door frames custom made in knock down, half knock down, and ready-made styles.

General Information & Terms

This **DraftSeal®** Catalogue supersedes all previous versions. Please visit **www.DraftSeal.com** for our full terms & conditions, freight, warranty, returns & allowances, claims policy, & other general information.

Product drawings throughout this catalogue are representations of the product size, dimensions, shape, etc. Changes & updates to this catalogue may occur without notice. This may include, but not limited to, specifications, product availability & product materials. A.K. Draft Seal Ltd. will not be held liable for any changes to this catalogue, or products depicted in this catalogue that may not match our CAD drawings.

A.K. Draft Seal Ltd. will not be liable for defects or damages arising from improper installation, product modification, incorrect application or storage of product. Written notice of damages must occur within the warranty period. Liability shall be limited to the replacement of product or component determined to be defective & shall not include costs arising from removal or reinstallation of product. Cost of replacement shall not exceed original purchase price. No other claims will be allowed. In no event shall liability be extended to include punitive, incidental or consequential damages arising from use of A.K. Draft Seal Ltd. products. This is the sole warranty given by A.K. Draft Seal Ltd. No other warranty implied or expressed shall be allowed.

By purchasing our products you agree to our Terms & Conditions herein stated.

INDEX

PROD #	PAGE #	PROD #	PAGE #	PROD #	PAGE #	PROD #	PAGE #
DSS11	35	DS176	11	DS339	33	DS1003TBA	17
DST33BL	34	DS177	19	DS340	33	DS1100HA	24, 25
DS61-50	43	DS177X4	16	DS341	33	DS1200HC	24, 25
DSS66	40, 35	DS177X5	16	DS342	26	DS1300HA	24, 25
DS67-50	43	DS177X6	16	DS343	33, 26	DS1400HA	24, 25
DS74-25	43	DS178	19	DS344	27	DS2000	10
DS76-12.5	43	DS179	41	DS351	21	DS2002	14
DS78-50	43	DS180	42	DS353	21	DS2220	14
DS79-12.5	43	DS181	42	DS369	39	DS2648	4, 23, 25
DS95	8	DS182	42	DS388	30	DS3330	14
DSS99D	35	DS183	42	DS400	14, 8	DS4000	9
DS100	34	DS184	40	DS401TBA	18	DS4000LA	10
DS103	38, 34	DS185	42	DS415	36	DS4001TBA	14
DS104	34	DS186	41	DS421	43	DS4440	14
DS110	28	DS187PS	41	DS422	37	DS5000	9
DS113	38, 34	DS188	40	DS424	37	DS5001TBA	14
DS116	36	DS200	14	DS434	43	DS5006SS	20
DS117	36	DS201	17	DS444	11, 12	DS5007SS	20
DS118	34	DS202TBA	17	DS444HA	13	DS5555	13
DS120	11	DS205TBI	17	DS500	8	DS6000	9
DS121	11	DS206TBI	14, 15	DS501TBA	18	DS6001TBA	14
DS130	32	DS210	30	DS510SS	10	DS6002TBA	14
DS131	33	DS211	30	DS555HA	13	DS6666	13
DS133	34	DS212	30	DS600	8	DS7000	9
DS136	29	DS216	30	DS600HA	10	DS7001TBA	15
DS137	38	DS217	30	DS601TBA	18	DS7777	13
DS138	29	DS222	11, 12	DS602TBA	18	DS8000	9
DS141	34	DS234	30	DS603TBA	17	DS8001TBA	15
DS140	28	DS236	12	DS606	20	DS9002TBA	15
DS144	28	DS236-4	12	DS666HA	13	DS10002TBA	15
DS147	38	DS275TBAT	17	DS700	8	DS11000	22, 23
DS148	38, 31	DS276TBAT	17	DS700HA	10	DS12000	22, 23
DS149	31	DS277X6	16	DS701TBA	18	DS13000	22, 23
DS150	31	DS277X7	16	DS703TBA	17	DS14000	22, 23
DS151	38	DS277X8	16	DS777HA	13	DS ROD	43
DS156	28	DS385	26	DS800	8	DS FIN-PILE	39
DS158	28	DS386	26	DS800HA	10	DS TAPES	43
DS161	31	DS333	11, 12	DS801TBA	18		
DS162	31	DS335	27	DS803TBA	17		
DS163	38	DS336	27	DS804TBA	17		
DS164	31	DS338	33	DS900HA	24, 25		
DS166	31			DS903TBA	17		
DS174	33			DS1000HA	24, 25		

General Information & Terms

This DraftSeal® Catalogue supersedes all previous versions. Please visit www.DraftSeal.com for our full terms & conditions, freight, warranty, returns & allowances, claims policy, & other general information.

Ordering

Please order material by catalogue number, specifying length required & number of pieces. Most weatherseals & thresholds are stocked in standard sizes & most are available in lengths up to 12 ft (3657mm). Thresholds are cut with 1/2" (12.7mm) to 1" (25.4mm) extra for trimming to size. For exact size, order threshold or weatherseal to specified length followed by "NET".

Thresholds ordered under 36" (914mm) will be charged as 36" (914mm).

Products ordered over 6 ft. (189mm) but under 9 ft. (2743mm) will be charged as 9 ft. (2743mm).

Products ordered over 9 ft. (2743mm) but under 12 ft. (3658mm) will be charged as 12 ft. (3658mm).

Please refer to DraftSeal full line price list for all product numbers, finishes, lineals, lengths & coil lengths.

Threshold Lengths

Thresholds are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths:

36-1/2" (927mm), 49" (1245mm), 73" (1854mm), 110" (2794mm), 147" (3734mm) stock length.

Extra wide thresholds 9" (229mm) and over are supplied punched unless otherwise specified.

Jamb & Header Weatherseal Lengths

Weatherseals are supplied with punched holes and screws and are only available in the following NET lengths / sets:

1/3' x 2/7' (914 x 2134mm) set, 1/3' x 2/8' (914 x 2438 mm) set, 1/6' x 2/7' (1829 x 2134mm) set, 3 x 8' (2438mm) set & 1 x 14' (4267mm) length

Door Bottom Sweep Lengths

Door bottom sweeps are supplied with punched holes and screws and are only available in the following NET lengths:

36" (914mm), 48" (1219mm), 84" (2134mm) & 96" (2438mm)

PVC Protective Tape



DS2648 PVC protective tape, apply to any sill or threshold. Purchase by roll. 6" (154mm), 8" (203mm), 12" (304mm) widths, 500' roll each.

Materials, Finishes & Fabrication

Aluminum

All aluminum extrusions are alloy 6063T5 & are furnished in mill finish (A). Some are available in clear anodized (C), bronze anodized (D).

Vinyl Inserts (flexible)

All cold temperature vinyl (p.v.c.) inserts are extruded from pure vinyl raw material.

TPE (T) inserts (flexible)

Some inserts are available in thermal plastic elastomer material. This TPE material has low temperature flexibility (remains flexible down to -80° Fahrenheit (-62° Celsius). It has excellent U.V. stability & resistance to compression set. It is designed for applications requiring non flammability. It also has good chemical resistance to alcohols, acids & bases.

Neoprene (Neoprene spec applies to certain products)

Synthetic rubber polymer blend: Polychloroprene & EPDM, very good abrasion resistance, tensile strength & memory, flame & moisture resistant. Temperature range -30° to 250° Fahrenheit (-34° to 121° Celsius). Good resistance to ozone, sunlight & aging; BHMA Certified to ANSI/BHMA A156.22 performance tests for Heat, Cold, Air Infiltration & Smoke Infiltration.

Silicone (Silicone spec applies to certain products)

Synthetic rubber polymer: Polysiloxane. Excellent flexibility & memory, flame & moisture resistant. Temperature range -100°F to 500°F, remains flexible at extreme temperatures. Excellent resistance to ozone, UV & aging. Recommended for areas using FM200 or Halon Fire Suppression Systems. BHMA Certified to ANSI/BHMA A156.22 performance tests for Heat, Cold, Air Infiltration & Smoke Infiltration.

Vinyl (rigid)

All PVC rigid profiles are extruded from PVC raw materials & are available in Solid Brown (B), White (W), Grey (G), Black (BL) & Sandstone (S) as indicated. Some profiles are extruded as Dual Durometer (flexible & rigid PVC fused together).

Screws

All thresholds are punched & countersunk for #10 Robertson flat head wood screws. Plated screws & plastic anchors of appropriate length are furnished with all aluminum & oak thresholds free of charge. All aluminum weatherseals are punched with slotted holes for #6 quad truss head self drilling screw. Plated screws of appropriate length are furnished with all weatherseals free of charge. Antique bronze-plated screws of appropriate length are furnished with all bronze anodized weatherseals & thresholds free of charge. Yellow zinc screws supplied with gold anodized & bright dip gold products.

Standard Finishes

A Mill finish aluminum	W Painted white aluminum
C Clear anodized aluminum	B Painted brown aluminum
D Bronze anodized aluminum	SS Stainless steel

Inserts

N Neoprene or rubber	S Silicone seal or sponge silicone
NB Nylon brush	V Vinyl
P Pile	T TPE (Thermoplastic elastomer)
R Sponge neoprene	

Insert Colors

BEIGE	Beige
GREY	Grey
BL	Black
TAN	Tan

Fabrication Options

RIP: Width **L-NOTCH:** Both ends of threshold **U-NOTCH:** Both ends of threshold

Custom Fabrication


Charges will apply for any ripping of thresholds, custom fabrication, custom drilling or punch pattern.

Product Testing & Classification Symbols

Symbols below & throughout this 2022 Catalogue are most up-to date & supersede all other information in print.

The Symbols below are shown adjacent to products throughout the catalogue to help identify products that meet specific ratings and/or code requirements. The 2 actual adhesive backed labels shown below are adhered to each of our rated products.

ACTUAL PRODUCT LABEL (NOT TO SCALE)




Tested in accordance with CAN/ULC S104, ASTM E-152, CFSM 43.7, NFPA 252-08, UBC 7-2-1997, UL 1784 (Formerly UBC 43-2-1991), UL 10(b) (2008).
Listed for Canada & USA - Fire Rated

Products indicated by this symbol are rated, listed & labelled as material for use on listed steel frames & listed swinging type fire doors of the hollow metal or steel covered composite type rated up to 1-1/2 hours. These products have been listed & labelled as a result of testing done by Warnock Hersey certifying that these products do not adversely affect the fire resistance of the door or frame. Products are regularly checked under the follow up factory inspection & certification service for manufacturing compliance with Warnock Hersey specifications. Contact A.K. Draft Seal Ltd. for further information.



Tested in accordance with UL 10(b) (2009) - Fire Tests of Door Assemblies, and CAN/ULC S104-10 - Standard Method for Fire Tests of Door Assemblies.

ACTUAL PRODUCT LABEL (NOT TO SCALE)



Tested in accordance with CAN/ULC S104, ASTM E-152, CFSM 43.7, NFPA 252-08, UBC 7-2-1994 (Formerly UBC 43-2-1991), UL 10(b) (2008).
Listed for Canada & USA - Fire Rated

These products have been listed & labelled as a result of testing done by Warnock Hersey certifying that these products do not adversely affect the fire resistance of the door or frame. Products are regularly checked under the follow-up factory inspection & certification service for manufacturing compliance with Warnock Hersey specifications. Contact A.K. Draft Seal Ltd. for further information. Thresholds or sills for use with listed wood frames & listed swinging type doors of wood or steel faced construction, 20 minute rated. Gasketing material for use on listed wood or steel frames & listed swinging type fire doors of wood or steel faced construction, 20 minute rated.



Smoke Tested to UL: 1784 (2015). Meets requirements for NFPA 105. Products indicated by this symbol are listed by Intertek as having been tested in accordance with Standard UL 1784 Air leakage tests of door assemblies, and meet the performance criteria for allowable air leakage as specified in NFPA 105 - Installation of Smoke Control Door Assemblies.



Barrier Free Meets requirements of ADAAG - 1998 & ICC / ANSI A177.1-1998. Products indicated by this symbol are access compliant by having installed height differences not over 1/2" (12.7mm) with allowable edge & slope conditions.



UL10B & CAN4-S104-80M Classified, Complies with NFPA 80 & NFPA 252 for application to Steel fire doors rated up to 3 Hrs., & Wood type fire doors rated up to 90 minutes. (Rating on some items vary & are noted.)



Positive Pressure UL10C Classified, Category 'J'; complies with IBC, NFPA 80 & NFPA 252 for application to Positive Pressure Steel fire doors rated up to 3 Hrs., & Wood type fire doors rated up to 90 minutes. (Ratings on some items vary & are noted.)



NGP-EDGE® Sealing System, Category 'G' classified; required for Category B classified wood type fire doors to meet positive pressure requirements complying with IBC, & NFPA 252. See individual products for maximum door size & ratings.



Smoke & Draft Control Gasketing, Category 'H' classified; complies with IBC, UL1784 & NFPA 105 for use on 'S' labeled Positive Pressure Steel fire doors rated up to 3 hours, & wood type fire doors rated up to 90 minutes. (Ratings on some items vary & are noted.)



Acoustical Tested to ASTM E90 standard test method for laboratory measurement of airborne sound transmission loss of building partitions & elements, & astm e1408 standard test method for laboratory measurement of the sound transmission loss of door panels & door systems.



Air Infiltration Tested to ASTM E283, standard test method for determining rate of air leakage through exterior windows, curtain walls, & doors.



Fire Rated 3 Hours















































Smoke Tested

























Air Infiltration Tested



Thresholds

PRODUCT TYPE	PROFILE EXAMPLE	ADA	RATED PROD. AVAILABLE	PAGE NUMBER
1/2" (12.7mm) rise thresholds				8
1/4" (6.4mm) low rise thresholds				9, 10
Specialty thresholds stainless steel & heavy duty				10
Stop strip & bumper thresholds				11
Floor transition & half thresholds				12
Low rise half & heavy duty half thresholds				13
Low rise thermally broken thresholds & components				14
Low rise thermally broken thresholds				15
Thermally broken thresholds & panic exit thresholds				16, 17
Thermally broken thresholds				18
Panic exit thresholds				19
Ramp thresholds & flat stainless steel thresholds				20
Oak thresholds				21
Specialty low rise thresholds 9" to 14" (229 to 356mm) extra wide				22, 23
Specialty thresholds 9" to 14" (229 to 356mm) extra wide				24, 25

Door Weatherseals, Sweeps, Meeting Stiles, Astragals

PRODUCT TYPE	PROFILE EXAMPLE	RATED PROD. AVAILABLE	PAGE NUMBER
Automatic door bottoms (surface & mortise)			26, 27
Door bottom sweeps			28, 29
Door shoes & door cap cap			30
Rain drips & brush door bottom sweeps			31
Jamb mounted weatherseals & sound seals			32-34
Jamb mounted sound seals			33
Adhesive backed / jamb gasket seals			35
Adhesive backed / jamb weatherseals & intumescent seals			36
Retrofit door weathersealing kits			37
Meeting stiles			38
Meeting stiles & fin pile seals			39
Astragals (flat & t-bar), security			40, 41, 42

Specialty Products

PRODUCT TYPE	PROFILE EXAMPLE	PAGE NUMBER
Multipurpose (neoprene & foam) adhesive backed tapes, fin pile		39, 43
DS2648 PVC protective tape, apply to any sill or threshold. Purchase by roll. 6" (154mm), 8" (203mm), 12" (304mm) widths, 500' roll, each		4, 23, 25

Residential Door Products

PRODUCT TYPE	PROFILE EXAMPLE	
Pre-hung door sill, sweeps, jamb seals, astragals & corner pads		Refer to DraftSeal residential catalogue

THRESHOLDS

1/2" (12.7mm) Rise Thresholds

1/2" (12.7mm)




4" (102mm)

DS400A Extruded aluminum mill finish
DS400D Bronze anodized


 **1-1/2 HR RATING**
.518 lbs./ft. (.771 kg/m)

1/2" (12.7mm)



5" (127mm)

DS95A Extruded aluminum mill finish

 **1-1/2 HR RATING**
.493 lbs./ft. (.734 kg/m)

1/2" (12.7mm)




5" (127mm)

DS500A Extruded aluminum mill finish
DS500D Bronze anodized


 **1-1/2 HR RATING**
.606 lbs./ft. (.902 kg/m)

1/2" (12.7mm)




6" (152mm)

DS600A Extruded aluminum mill finish
DS600D Bronze anodized


 **1-1/2 HR RATING**
.747 lbs./ft. (1.112 kg/m)

1/2" (12.7mm)



7" (178mm)

DS700A Extruded aluminum mill finish
DS700D Bronze anodized

 **1-1/2 HR RATING**
.913 lbs./ft. (1.359 kg/m)

1/2" (12.7mm)



8" (203mm)
product not shown full width

DS800A Extruded aluminum mill finish
DS800D Bronze anodized


 **1-1/2 HR RATING**
1.158 lbs./ft. (1.724 kg/m)

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm




THRESHOLDS

1/4" (6.4mm) Low Rise Thresholds



Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm




THRESHOLDS

Specialty Thresholds

3/16" (4.7mm)

2-1/4" (57mm)





DS2000A

Extruded aluminum mill finish

DS2000D

Bronze anodized




1-1/2 HR
RATING

.259 lbs./ft. (.386 kg/m)

1/8" (3mm)


4" (102mm)



DS4000LA

Extruded aluminum mill finish. Holes are punched & staggered when specified.

Length available: 12ft (3658mm) only. **Note: Special order only, minimum run required 1500LF**



1-1/2 HR
RATING

.346 lbs./ft. (.515 kg/m)

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

Stainless Steel

1/2" (12.7mm)

5" (127mm)



DS510SS

Stainless steel, 304 SS brushed finish. Lengths available: 36-1/2" (927mm) 73" (1854mm) 120" (3048mm).




1-1/2 HR
RATING

Heavy Duty (H) Thresholds (Mill finish is standard. Bronze anodized available on custom order)



1/2" (12.7mm)

6" (152mm)



DS600HA

Extruded aluminum heavy duty, mill finish




1-1/2 HR
RATING

1.312 lbs./ft. (1.952 kg/m)



1/2" (12.7mm)

7" (178mm)



DS700HA

Extruded aluminum heavy duty, mill finish




1-1/2 HR
RATING

1.38 lbs./ft. (2.054 kg/m)



1/2" (12.7mm)

8" (203mm)
product not shown full width



DS800HA

Extruded aluminum heavy duty, mill finish




1-1/2 HR
RATING


1.662 lbs./ft. (2.473 kg/m)

THRESHOLDS

Stop Strip (Threshold Applied)



DST17BL
Replacement TPE
(T) insert black, for
DS176N




DS176AT Extruded aluminum mill finish with TPE (T) insert, black, rated
(Threshold not included, order separately)


DS176AP Extruded aluminum mill finish with pile insert,
grey, **not rated**. Threshold not included, order separately

Bumper strip may be fastened to various DS thresholds to accommodate vertical rod panic hardware, where wide panic exit thresholds are required.

Bumper Thresholds




DS121AV Extruded aluminum mill finish with vinyl insert, grey
DS121AVBL Mill finish with vinyl insert, black
DS121WV White with grey insert
DS121BVBL Brown with black insert



DS120AV Extruded aluminum mill finish with vinyl insert, grey
DS120AVBL Mill finish with black insert
DS120DVBL Bronze anodized with black insert



DSV20GREY
Replacement vinyl insert, grey
for DS120, DS121 & DS121
DSV20BL Black



DS222AV Extruded aluminum mill finish with vinyl insert, grey
DS222DV Bronze anodized



DSV22GREY
Replacement vinyl insert, grey
for DS222V, DS333V & DS444V



DS333AV Extruded aluminum mill finish with vinyl insert, grey
DS333DV Bronze anodized




DS444AV Extruded aluminum mill finish with vinyl insert, grey
DS444DV Bronze anodized

Thresholds on this page are supplied with
punched countersunk holes with screws
and plugs and are only available in the
following NET lengths (except as noted):


36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

THRESHOLDS

Floor Transition Thresholds



DS236A Extruded aluminum mill finish
DS236D Bronze anodized




DS236-4A Extruded aluminum mill finish
DS236-4D Bronze anodized

Floor transition thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths:

36-1/2"	927mm
73"	1854mm

Half Thresholds



DS222A Extruded aluminum mill finish
DS222D Bronze anodized



Barrier free, ADA compliant if used as above



DS333A Extruded aluminum mill finish
DS333D Bronze anodized



DS444A Extruded aluminum mill finish
DS444D Bronze anodized



Half thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm




THRESHOLDS

Low Rise Half Thresholds **NOTE:** Thresholds on this page are non-returnable. Manufacturing time required for bronze anodized finish.

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in these NET lengths (except as noted): 36-1/2" (927mm), 110" (2794mm), 49" (1245mm), 147" (3734mm) & 73" (1854mm)




Heavy Duty Half Thresholds




THRESHOLDS


Low Rise Half Thresholds / Components




DS4440A Extruded aluminum mill finish



DS3330A Extruded aluminum mill finish




DS2220A Extruded aluminum mill finish





DS2002A Extruded aluminum mill finish


Thermally Broken 1/4" (6.4mm) Low Rise Thresholds




DS4001TBA Extruded aluminum mill finish, thermally broken



DS5001TBA Extruded aluminum mill finish, thermally broken







DS6001TBA Extruded aluminum mill finish, thermally broken




DS6002TBA Extruded aluminum mill finish, thermally broken

Thermally Broken 1/4" (6.4mm) Low Rise Thresholds




THRESHOLDS

Latching Panic Exit, Thermally Broken (TB) Thresholds




DST17BL
Replacement
TPE (T) insert,
black

DS177X4TBAN Mill finish with vinyl thermal break & TPE (T) insert, black (rated)




DS177X5TBAN Mill finish with vinyl thermal break & TPE (T) insert, black (rated)




DS177X6TBAN Mill finish with vinyl thermal break & TPE (T) insert, black (rated)



DS277X6TBAT Mill finish with vinyl thermal break & TPE (T) insert, black (rated)




DS277X7TBAT Mill finish with vinyl thermal break & TPE (T) insert, black (rated)



DS277X8TBAT Mill finish with vinyl thermal break & TPE (T) insert, black (rated)

THRESHOLDS


Thermally Broken Threshold Components




DS201A Extruded aluminum mill finish
DS201D Bronze anodized




DS202TBA Extruded aluminum mill finish with thermal break insert



DS205TBI Extruded rigid pvc vinyl insert, grey, for thermally broken thresholds



DS275TBAT Extruded aluminum mill finish with vinyl thermal break insert & TPE (T) insert



DS276TBAT Extruded aluminum mill finish with vinyl thermal break insert & TPE (T) insert




Thermally Broken Thresholds



DS603TBA Extruded aluminum mill finish with 2 thermal breaks



NOTE: By adding multiples of **DS202TBA**, wider thresholds may be achieved, consult factory. By adding **DS275TBA** (Panic Stop), wider Panic Thresholds may be achieved, consult factory.



DS703TBA Extruded aluminum mill finish with 2 thermal breaks, 7-1/4" (184mm) wide



DS803TBA Extruded aluminum mill finish with 2 thermal breaks, 8-1/4" (209mm) wide



DS804TBA Extruded aluminum mill finish with 2 thermal breaks, 8-1/4" (209mm) wide



DS804TBD Bronze anodized



DS903TBA Extruded aluminum mill finish with 2 thermal breaks, 9-1/4" (235mm) wide




DS1003TBA Extruded aluminum mill finish with 2 thermal breaks, 10-1/4" (260mm) wide




THRESHOLDS


Thermally Broken Thresholds 1/2" (12.7mm) Rise



DS401TBA Extruded aluminum mill finish with vinyl thermal break




DS501TBA Extruded aluminum mill finish with vinyl thermal break




DS601TBA Extruded aluminum mill finish with vinyl thermal break



DS602TBA Extruded aluminum mill finish with vinyl thermal break



DS701TBA Extruded aluminum mill finish with vinyl thermal break




DS801TBA Extruded aluminum mill finish with vinyl thermal break

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

THRESHOLDS


Latching Panic Exit Thresholds



DST17BL
Replacement TPE
(T) insert black, for
DS177 & DS178

DS177AT Mill finish with TPE (T) insert, black (rated)

DS177DT Bronze with TPE (T) insert, black (rated)




DS178AT Mill finish with TPE (T) insert, black (rated)


DS178DT Bronze with TPE (T) insert, black (rated)

THRESHOLDS

Ramp Thresholds




DS606A Extruded aluminum mill finish
Note: Max 6' only



DS605DS606A36 Extruded aluminum (2 piece ramp joined)
Note: Special order only. Max 6' only.
Aprox. 10 week production

Flat Thresholds, Stainless Steel (Custom order, manufacturing time)

Available in 304 stainless steel 14 gauge with a #4 brushed finish. Drawings showing sizes, end notch outs & mounting holes (if needed) are required with order.






***Special Order Only**
4-6 weeks

THRESHOLDS

Oak Thresholds

ALL OAK PROFILES SHOWN ON THIS PAGE CAN BE RIPPED FOR CUSTOM APPLICATIONS.



#10 Antique Bronze plated Robertson flat head wood screws & plastic anchors of appropriate length are supplied with all DraftSeal oak thresholds. All oak thresholds are supplied not drilled unless drilling instructions are specified with order.



THRESHOLDS

Low Rise Extra Wide Thresholds

NOTE: Thresholds on this page are non-returnable. Manufacturing time required for bronze anodized finish. Bronze anodized only available up to 12 ft (3658mm).





DS2648 PVC protective tape, apply to any sill or threshold.
Purchase by roll. 4" (101mm), 6" (154mm), 8" (203mm), 12" (304mm) widths.

Wide thresholds on this page 9" to 14" (229 to 356mm) are available in the following NET lengths:


36-1/2"	(927mm)
49"	(1245mm)
73"	(1854mm)
110"	(2794mm)
147"	(3734mm)

Extra wide thresholds are standard punched or drilled unless otherwise specified.


THRESHOLDS

Extra Wide Heavy Duty (H) Thresholds

NOTE: Thresholds on this page are non-returnable. Manufacturing time required for bronze anodized finish.




DS900HA (2 piece) extruded aluminum mill finish, not welded




DS1000HA (1 piece) extruded aluminum mill finish
DS1000HD (1 piece) bronze anodized



DS1200HC (1 piece) extruded aluminum clear anodized




DS1300HA (2 piece) extruded aluminum mill finish, not welded



DS1400HA (2 piece) extruded aluminum mill finish, not welded



DS2648 PVC protective tape, apply to any sill or threshold.
Purchase by roll. 4" (101mm), 6" (154mm), 8" (203mm), 12" (304mm) widths.



Wide thresholds on this page 9" to 14" (229 to 356mm) are available in the following NET lengths:


36-1/2"	(927mm)
49"	(1245mm)
73"	(1854mm)
110"	(2794mm)
147"	(3734mm)

Extra wide thresholds are standard punched or drilled unless otherwise specified.



AUTOMATIC DOOR BOTTOMS


Surface Mounted Application



DS343CN Extruded aluminum clear anodized with neoprene insert, black

DS343DN Bronze anodized, 36" & 48" only (914mm & 1219mm)

Surface Mounted Application



DS385CN24 Extruded aluminum clear anodized with neoprene insert, black


DS385CN32 Extruded aluminum clear anodized with neoprene insert, black

DS385CN36 Extruded aluminum clear anodized with neoprene insert, black

DS385CN42 Extruded aluminum clear anodized with neoprene insert, black

DS385CN48 Extruded aluminum clear anodized with neoprene insert, black


Mortise Application



DS342AN Extruded aluminum mill finish with neoprene insert, black. Available with lead insert for radiation shield. Specify "lead lined" custom order, call for manufacturing time.

DS342EC End plate (replacement part)

Mortise Application



DS386AN24 Extruded aluminum mill finish with neoprene insert, black

DS386AN32 Extruded aluminum mill finish with neoprene insert, black


DS386AN36 Extruded aluminum mill finish with neoprene insert, black

DS386AN42 Extruded aluminum mill finish with neoprene insert, black

DS386AN48 Extruded aluminum mill finish with neoprene insert, black

AUTOMATIC DOOR BOTTOMS

Mortise Application for Metal Doors



Lengths available:


24" (610mm) special order only
 28" (711mm)
 30" (762mm)
 32" (813mm)
 36" (914mm)
 42" (1067mm)
 48" (1219mm)

DS344AN Extruded aluminum mill finish with neoprene insert, black.

Fits in 1 5/8" x 3/4" (41mm x 19mm) bottom door channel & may be field cut (up to 4" [102mm]) in length to fit door & is reversible. This unit has an adjusting screw to regulate amount of drop to 1/2" (12.7mm). A "furring strip" may be used to lower this automatic door bottom when a deeper channel is used. Units furnished 1/2" (12.7mm) shorter than ordered length in order to fit within net door size. Door Bottoms lengths available from 24" (610mm) - 48" (1219mm). Fire ratings apply to metal doors only.

Mortise Application

5/8" x 1-9/16" (16mm x 40mm)




DS336AN Extruded aluminum mill finish with neoprene insert, black

Lengths available:

23-3/4" (603mm) special order only
 27-3/4" (705mm)
 29-3/4" (756mm)
 31-3/4" (806mm)
 35-3/4" (908mm)
 41-3/4" (1060mm)
 47-3/4" (1213mm)


Surface Mounted Application



DS335CN Extruded aluminum clear anodized with neoprene insert, black
DS335DN Bronze anodized with neoprene insert, black. Custom order, call for manufacturing time. 36" & 48" only (914mm & 1219mm)

* The **EZ-Touch** door bottom requires only 3 to 5 pounds of pressure to activate the drop bar mechanism. Light gauge materials have allowed us to perfect a door bottom suited for those applications when the pressure to close the door is critical. We've included the same proven technology used in all of our other automatic door bottoms. Accessibility requirements remind us of the necessity for everyone to be able to operate doors with ease. Our EZ-Touch door bottom meets that need & still provides an effective seal for any application. End caps furnished standard.

DOOR BOTTOM SWEEPS




DS140AV Extruded aluminum mill finish with vinyl insert, grey

DS140DV Bronze anodized with black insert

DS140WV Painted white with grey insert

DSV40BL Replacement black insert

DSV40GREY Replacement grey insert




DS156AV Extruded aluminum mill finish with vinyl insert, grey

DS156DV Bronze anodized with grey insert

DS156WV Painted white with grey insert


DSV56GREY Replacement grey insert



DS110AP Extruded aluminum mill finish with pile insert, black

DS110DP Bronze anodized


DSP10BL Replacement pile insert, black



DS144AP Extruded aluminum mill finish with fin pile insert



DS7545-270G
Replacement fin pile insert grey



Sweep With
Snap-On Cover
To Conceal
Screws



DS158A Extruded aluminum mill finish with nylon brush insert, black.
Lengths available: 36" (914mm) & 48" (1219mm)



DS158C Clear anodized

DS158D Bronze anodized

DS158W Painted white


DSBRUSH716BL Replacement brush insert, black

WEATHERSEALS (OVERHEAD, SLIDING & GARAGE DOOR)




DS144AP Extruded aluminum mill finish with fin pile insert


DOOR BOTTOM SWEEPS




DS138C-2 Extruded aluminum clear anodized with rubber insert, black, 1/8" x 2" (3.2mm x 51mm)
DS138D-2 Bronze anodized



DS138C Extruded aluminum clear anodized with rubber insert, black, 1/8" x 1-3/8" (3.2mm x 35mm)
DS138D Bronze anodized




DS136C Extruded aluminum clear anodized with rubber insert, black, 1/8" x 1-3/8" (3.2mm x 35mm)
DS136DN Bronze anodized



DS238SSN Stainless steel with rubber insert, black

***Special Order Only**

Proper installation using a DS138 or equivalent sweep with a threshold




Door bottom sweeps on this page are supplied with punched holes and screws and are only available in the following NET lengths:


36" (914mm)
 48" (1219mm)
 84" (2134mm)
 96" (2438mm)

DOOR SHOES (ALUMINUM)


Door shoes on this page are supplied with punched holes and screws and are available in the following NET lengths: 36" (914mm) & 48" (1219mm). Custom lengths available, call for manufacturing time.




DS211AT Extruded aluminum mill finish with TPE (T) insert
DS211DT Bronze anodized




DS210AT Extruded aluminum mill finish with TPE (T) insert
DS210DT Bronze anodized




DS217AT Extruded aluminum mill finish with TPE (T) insert
DS217DT Bronze anodized



DS216AT Extruded aluminum mill finish with TPE (T) insert
DS216DT Bronze anodized



DS212AT Extruded aluminum mill finish with TPE (T) insert
DS212DT Bronze anodized




DS234AT
Extruded aluminum mill finish with TPE (T) insert




DS216BL
Replacement TPE (T) insert, black, for products on this page

Door Top Cap For Hollow Metal Doors




DS388 Extruded rigid vinyl grey.
Length available: 9 ft. (2743mm) only


RAIN DRIPS




DS164A Extruded aluminum mill finish.
Lengths available:
36" (914mm) & 48" (1219mm)
DS164D Bronze anodized



DS166C42 Extruded aluminum clear anodized, 42" (1067mm) length
DS166C54 Clear anodized, 54" (1372mm) length
DS166C84 Clear anodized, 84" (2134mm) length
DS166C168 Clear anodized, 168" (4267mm) length




DS161ANB Extruded aluminum mill finish
with nylon brush insert, black. Lengths
available: 36" (914mm) & 48" (1219mm)
DS161DNB Bronze anodized




DS162AV Extruded aluminum mill finish with vinyl insert,
grey. Lengths available: 36" (914mm) & 48" (1219mm)
DS162DV Bronze anodized

NYLON BRUSH (NB) DOOR BOTTOM SWEEPS - UBC 7-2 (1997) When Used As A Door Bottom Sweep Only


Lengths available: 36" (914mm), 48" (1219mm), 84" (2134mm) & 96" (2438mm).




DS148CNB Clear anodized with brush insert
DS148DNB Bronze anodized




DS149CNB Clear anodized with brush insert
DS149DNB Bronze anodized



DS150CNB Clear anodized with brush insert
DS150DNB Bronze anodized



- DS130CR** Extruded aluminum clear anodized with sponge neoprene insert
- DS130DR** Bronze anodized
- DS437BL** Replacement neoprene sponge insert, black, 1/4" x 1/2" (6.4mm x 12.7mm)



- DS243SSR** Stainless steel with sponge neoprene insert.
- DSR43BL** Replacement neoprene sponge insert, black 3/4" x 3/16" (19mm x 5mm) thick

Weatherseals on this page are supplied with punched holes and screws and are only available in the following NET lengths:

1/3' x 2/7' set	(914 x 2134mm)
1/3' x 2/8' set	(914 x 2438 mm)
1/6' x 2/7' set	(1829 x 2134mm)
3 x 8' set	(2438mm)
1 x 14' length	(4267mm)


***Special Order Only**

ADJUSTABLE-JAMB SOUND SEALS


Sound Transmission Class (STC) Rated Door Assemblies

STC RATING ON DOOR	STC RATING DOOR WITH GASKET	PERIMETER SEALS	AUTOMATIC DOOR BOTTOM	THRESHOLD
STC 30	30	DS340 or DS339	DS343CR	DS174N
STC 40	37	DS340 or DS339	DS343CR	DS174N
STC 50	43	DS340	DS343CR	DS174N


Weatherseals and sound seals on this page are supplied with punched holes and screws and are available in the following NET lengths / sets: 1/36" x 2/84" set (914 x 2134mm). Custom lengths available, call for manufacturing time.




DS340CN17 Extruded aluminum clear anodized with neoprene insert, black



DS339CN17 Extruded aluminum clear anodized with neoprene insert, black




DS341CN Clear anodized with neoprene insert, black
DSN41BLACK Replacement neoprene insert, black



DS338CN Clear anodized with neoprene insert, black
DS338DN Bronze anodized
DSR38BLACK Replacement neoprene insert, black

DOOR WEATHERSEALING


Dual Screw Mounting



DS131CN17 Extruded aluminum clear anodized with 3/8" x 1-1/4" (9.5mm x 32mm) neoprene insert


Note: Lead time is 8-11 weeks

DOOR WEATHERSEALING, HOLLOW BULB



Snap-On Cover To Conceal Screws


DS113CS Extruded aluminum clear anodized with silicone insert, black



DS133CT Extruded aluminum clear anodized with TPE (T) insert, black

DS133DT Bronze anodized


DST33BL Replacement TPE (T) insert, black



DS103AT Extruded aluminum mill finish with TPE (T) insert

DS103DT Bronze anodized

DST03BL Replacement TPE (T) insert, black



DS104AV Extruded aluminum mill finish with cold temp vinyl insert

DS104WV Painted white

DS104AV17 Mill finish set 1/36\" x 2/84\"

DS104AV20 Mill finish set 1/72\" x 2/84\"

DSV04GREY Replacement vinyl insert, grey

Weatherseals on this page are supplied with punched holes & screws and are available in the following NET lengths / sets:

1/3' x 2/7' set (914 x 2134mm)


1/3' x 2/8' set (914 x 2438 mm)

1/6' x 2/7' set (1829 x 2134mm)

3 x 8' set (2438mm)

1 x 14' length (4267mm)


Certain products are not available in all sizes listed, refer to price list.




Perimeter seal compatible with parallel arm closers

DS118CT Extruded aluminum clear anodized with TPE (T) insert

DST03BL Replacement TPE (T) insert, black.



DS141CT Extruded aluminum clear anodized with TPE (T) insert, black




DS100AT Extruded aluminum mill finish with TPE (T) insert

DS100DT Bronze anodized


DST00BL Replacement TPE (T) insert, black

ADHESIVE-BACKED GASKET SEALS

Triple Fin Silicone Adhesive-Backed Fire Rated Gasketing



DSS99 Application Details




DSS99D3 bronze colour, 1/36" (5.18m)	DSS99D8 bronze colour, 1/96" (93.2m)	DSS99D20 bronze colour, 1/6 ft x 2/7 ft
DSS99D6 bronze colour, 1/72" (6.40m)	DSS99D17 bronze colour, 1/3 ft x 2/7 ft	DSS99D21 bronze colour, 3/7 ft
DSS99D7 bronze colour, 1/84" (7.62m)	DSS99D19 bronze colour, 1/3 ft x 2/8 ft	DSS99D24 bronze colour, 3/8 ft

Silicone Adhesive-Backed Fire Rated Gasketing

For Wood Door & Metal Frame


This design is for those applications with very tight clearances from door edge to jamb & the pressure to close the door is critical.



Bronze

DSS11D17 17 ft. (5.18m)	DSS11D25 25 ft. (7.62m)
DSS11D21 21 ft. (6.40m)	DSS11D306 306 ft. (93.2m)

For Hollow Metal Door & Metal Frame




Bronze

DSS66D17 17 ft. (5.18m)	DSS66W17 17 ft. (5.18m)
DSS66D21 21 ft. (6.40m)	DSS66W21 21 ft. (6.40m)
DSS66D25 25 ft. (7.62m)	DSS66W25 25 ft. (7.62m)
DSS66D306 306 ft. (93.2m)	DSS66W306 306 ft. (93.2m)

Santoprene Adhesive-Backed Gasketing

For Wood Door & Metal Frame


This design is for those applications with very tight clearances from door edge to jamb & the pressure to close the door is critical.



Bronze

DS22D17 17 ft. (5.18m)	DS22D25 25 ft. (7.62m)
DS22D21 21 ft. (6.40m)	DS22D515 515 ft. (156.97m)


For Hollow Metal Door & Metal Frame



Bronze


DS77D17 17 ft. (5.18m)
DS77D21 21 ft. (6.40m)
DS77D25 25 ft. (7.62m)
DS77D515 515 ft. (156.97m)

DSS11, DSS66, DS22 & DS77 Application Details




ADHESIVE-BACKED JAMB SEALS


Vinyl-Flex (Compression) Seal, Adhesive-Backed




DS117T84 tan, 84" (2134mm) only
DS117W84 white




DS116T84 tan, 84" (2134mm) only
DS116W84 white



Compression Seal, Adhesive-Backed




DS415BL144 black, 144" (3658mm)



RETROFIT DOOR WEATHERSEALING

Superior Plus Weathersealing Door Kit E-Lon® by Foam Tite®




DS422B Extruded aluminum painted brown with gasket insert, brown
DS422C Clear anodized with black gasket insert
DS422W Painted white with white gasket insert

Available in sets of

1/36" x 2/81" (914 x 2057mm) single door set
 1/36" x 2/84" (914 x 2134mm) single door set
 1/81" x 2/84" (2057 x 2134mm) double door set

Advantages Of Foam-Tight Kerf Gasket


- » Closed cell foam structure: high resistance to water absorption & eliminates wicking.
- » Seamless elastomeric skin: provides long life, resilience, & durability. Puncture & tear resistant, outlasts & outperforms all other replacement weathersealing.
- » Superior resistance to compression set: operating forces remain constant over a wide compression range, helping doors exceed all industry requirements.
- » Performance: independent tests have shown foam-tight performs like new under all temperature.
- » Punched/slotted holes.
- » Plated screws supplied with white sets.
- » Antique bronze plated screws supplied with brown sets.
- » Foam-Tight gasket easily replaceable, pull out the old & push in the new.



DS422

Extruded aluminum painted brown or white, with matching brown or white foam-tight compression gasket. Also available clear anodized extrusion with black foam-tight compression gasket.


Superior Weathersealing Door Kit



DS424D16.5 Painted brown with brown gasket, 1/36" x 2/81" (914 x 2057mm) single door set
DS424D17 Painted brown with brown gasket, 1/36" x 2/84" (914 x 2134mm) single door set
DS424D20 Painted brown with brown gasket, 1/81" x 2/84" (2057 x 2134mm) double door set
DS424D96 Painted brown with brown gasket, 1/96" (2438mm) one piece only
DS424C16.5 Clear anodized with black gasket, 1/36" x 2/81" (914 x 2057mm) single door set
DS424C17 Clear anodized with black gasket, 1/36" x 2/84" (914 x 2134mm) single door set
DS424C20 Clear anodized with black gasket, 1/81" x 2/84" (2057 x 2134mm) double door set
DS424C96 Clear anodized with black gasket, 1/96" (2438mm) one piece only
DS424W16.5 Painted white with white gasket, 1/36" x 2/81" (914 x 2057mm) single door set
DS424W17 Painted white with white gasket, 1/36" x 2/84" (914 x 2134mm) single door set
DS424W20 Painted white with white gasket, 1/81" x 2/84" (2057 x 2134mm) double door set
DS424W96 Painted white with white gasket, 1/96" (2438mm) one piece only

MEETING STILES

Meeting stiles on this page are supplied with punched holes and screws and are available in the following NET lengths: 84" (2134mm) & 96" (2438mm). Custom lengths available, call for manufacturing time.




DS137CT Extruded aluminum clear anodized with TPE (T) insert. Sold in single units, order 2 lengths for meeting stile. Not rated for meeting stiles.

DS137DT Bronze anodized

DST37BL Replacement TPE (T) insert, black

Smoke-Rated Astragal Sets


Fire-rated Astragal Seals cannot replace any astragal required on the door by the door manufacturer to maintain its fire label. IBC, NFPA 80, NFPA105, NFPA 252 require the gap at the meeting edge between fire labeled doors must not exceed 1/8".



DS147CN Extruded aluminum clear anodized with neoprene insert. Sold in single units, order 2 lengths for meeting stile.

Spring Adjustable Astragal Sets


- Adjustment screws on 10" centers allow adjustment of the seal without re-positioning mounting location.
- Spring-loaded to maintain constant pressure for the most effective seal



DS151C Extruded aluminum clear anodized (no pile insert). Sold in single units, order 2 lengths for meeting stile.


DS151CP Clear anodized with polypropylene pile insert.

 Up to 3 hrs. metal doors, 20 mins wood doors




DS103AT Extruded aluminum mill finish with TPE (T) insert. Sold in single units, order 2 lengths for meeting stile. Not rated for meeting stiles.

DS103DT Bronze anodized




DS148CNB Extruded aluminum clear anodized with nylon brush insert. Sold in single units, order 2 lengths for meeting stile. Not rated for meeting stiles

DS148DNB Bronze anodized



DS163CNB Clear anodized with nylon brush insert. Sold in single units, order 2 lengths for meeting stile.

DS163DNB Bronze anodized




Snap-on cover to conceal screws

DS113CP Extruded aluminum clear anodized with nylon brush insert, grey. Sold in single units, order 2 lengths for meeting stile.

DS113DP Bronze anodized


MEETING STILES

Extrusion Only, No Insert




DS369A

Extruded aluminum mill finish t-slot extrusion only (no insert) drilled & countersunk. Inserts with .270 (6.85mm) backing will fit this t-slot extrusion.




Meeting stile application

NO SCALE



Door bottom sweep application

NO SCALE



DS369AT Extruded aluminum mill finish with TPE (T) insert

DS369DT Bronze anodized




DST17BL


Replacement TPE (T) insert black, for DS369

T-Slot Extrusion With Fin Pile Inserts (Choice of 6 overall heights).


Lengths available for DS369: 36" (914mm), 48" (1219mm), 84" (2134mm), 96" (2438mm) & 180" (4572mm)



DS369A7520G Aluminum extrusion mill finish with fin pile insert, grey




DS369A7530G Aluminum extrusion mill finish with fin pile insert, grey
DS369A7130BL Black pile, no fin




DS369A7535G Aluminum extrusion mill finish with fin pile insert, grey



DS369A7540G Aluminum extrusion mill finish with fin pile insert, grey



DS369A7545G Aluminum extrusion mill finish with fin pile insert, grey
DS369A7445W with fin pile insert, white
DS369A7145BL with fin pile insert, black



DS369A7550G Aluminum extrusion mill finish with fin pile insert, grey

Pile Weatherseal Insert Only

Polypropylene Pile, Fin & Backing

3/16" = 4.7mm

1/4" = 6.4mm

5/16" = 8mm

3/8" = 9.5mm

7/16" = 11mm

1/2" = 12.7mm

Fin-Pile Only



Available in footage or full coils

- * **DS7520-270G** .270" wide backing - 3/16" grey pile height with fin
- * **DS7530-270G** .270" wide backing - 1/4" grey pile height no fin
- * **DS7130-270BL** .270" wide backing - 1/4" black pile height with fin
- * **DS7535-270G** .270" wide backing - 5/16" grey pile height with fin
- * **DS7540-270G** .270" wide backing - 3/8" grey pile height with fin
- * **DS7545-270G** .270" wide backing - 7/16" grey pile height with fin
- * **DS7445-270W** .270" wide backing - 7/16" white pile height with fin
- * **DS7145-270BL** .270" wide backing - 7/16" black pile height with fin
- * **DS7550-270G** .270" wide backing - 1/2" grey pile height with fin

DS7620-187G 3/16" wide backing - 3/16" grey pile height with fin


DS7630-187G 3/16" wide backing - 1/4" grey pile height with fin

* Product numbers marked with asterisk fit into **DS369A** T-Slot extrusion. See top of this page.


- » High performance pile with a solid center fin barrier provides maximum resistance to air, water & dust infiltration.
- » Recommended pile compression 10%.
- » Excellent performer in sliding applications.

ASTRAGALS (OVERLAPPING)


Flat bar astragals, drilled (supplied with thru-bolts)



DS184SSATIN Flat bar, **STAINLESS STEEL**. Lengths available: 84" (2134mm), 96" (2438mm), 144" (3658mm)
DS188-2PS Flat bar, **STEEL** prime coated 2" (51mm) wide. Lengths available: 84" (2134mm), 96" (2438mm), 144" (3658mm)




DS188-3PS Flat bar, steel prime coated 3" (76mm) wide, 84" only.




DS188-4PS Flat bar, steel prime coated 4" (102mm) wide, 84" only.

HIGH SECURITY ASTRAGALS



Flat bar astragals, drilled (supplied with thru-bolts)




DS186PS Steel prime coated, custom. Lengths available 84" (2134mm)



DS187PS Steel prime coated, standard.
Lengths available 84" (2134mm)



Continuous security latch protector, full height of door.




DS179PS Steel prime coated, pre-drilled. Lengths available: 84" (2134mm)

ASTRAGALS

Flat & T-Bar

Lengths available for DS180, DS182 and DS185: 84" (2134mm), 96" (2438mm) & 180" (4572mm)



DS185CP

Extruded aluminum clear anodized with pile insert

DS185DP

Bronze anodized



DS7520-270G

Replacement Pile insert, grey for DS180 & DS185



DS185CT

Extruded aluminum clear anodized with TPE (T) insert


DS185DT

Bronze anodized




DST17BL Replacement


TPE insert, black for DS180 & DS185



DS180CP Extruded aluminum clear anodized with pile insert



DS180CT Extruded aluminum clear anodized with TPE (T) insert



DS182 Extruded aluminum clear anodized with TPE (T) insert

DS182CT84 Clear anodized 84" (2134mm)


DS182CT96 Clear anodized 96" (2438mm)

DS182CT180 Clear anodized 180" (4572mm)

DS182DT84 Bronze anodized 84" (2134mm)

DS182DT96 Bronze anodized 96" (2438mm)


DS182DT180 Bronze anodized 180" (4572mm)



DS181D Bronze anodized with neoprene gasket. Lengths available: 84" (2134mm) & 96" (2438mm)

DS181C Clear anodized

DS181W Painted white



DS183 Extruded aluminum with TPE (T) insert

DS183CT84 Clear anodized 84" (2134mm)

DS183CT96 Clear anodized 96" (2438mm)

DS183DT84 Bronze anodized 84" (2134mm)

DS183DT96 Bronze anodized 96" (2438mm)


DS183WT84 Painted white 84" (2134mm)

DS183WT96 Painted white 96" (2438mm)




WEATHERSEALING (KERF-INSERTED)

DS434 Q-Foam Wrap Kerf Inserted Jamb Weatherseal



DS434B81	Brown 81" (2057mm)
DS434B97	Brown 97" (2464mm)
DS434BL81	Black 81" (2057mm)
DS434BL97	Black 97" (2464mm)
DS434W81	White 81" (2057mm)
DS434W97	White 97" (2464mm)

E-Lon® .650 by Foam Tite® DS421 Kerf Inserted Jamb Weatherseal



DS421BL

Black. Lengths: 37", 82", 86", 97"

Full coil: 500 ft. (152m) or custom size coil up to 500 ft.

DS421B

Brown. Lengths: 37", 82", 86", 97"

Full coil: 500 ft. (152m) or custom size coil up to 500 ft.

DS421W

White. Lengths: 37", 82", 86", 97"

Full coil: 500 ft. (152m) or custom size coil up to 500 ft.

MULTI-PURPOSE WEATHERSEAL TAPES

Packaged Rolls



All adhesive backed tapes have a limited shelf life. These products must be used within 6 months of purchase & must be stored between 50° & 100° Fahrenheit (10° & 37.77° Celsius).

Open Cell Polyurethane A/B Tapes

DS831R	3/16" thick	x 3/8" wide	x 16.5 ft. grey	(4.7mm x 9.5mm x 5.02m)
DS835R	1/4" thick	x 1/2" wide	x 16.5 ft. grey	(6.4mm x 12.7mm x 5.02m)
DS837R	3/8" thick	x 3/8" wide	x 16.5 ft. grey	(9.5mm x 9.5mm x 5.02m)

Neoprene Closed Cell Sponge A/B Tapes

DS861R	3/16" thick	x 3/8" wide	x 10 ft. black	(4.7mm x 9.5mm x 3.04m)
DS863R	1/4" thick	x 1/2" wide	x 10 ft. black	(6.4mm x 12.7mm x 3.04m)
DS864R	5/16" thick	x 3/8" wide	x 10 ft. black	(8mm x 9.5mm x 3.04m)
DS865R	5/16" thick	x 3/4" wide	x 10 ft. black	(8mm x 19mm x 3.04m)
DS866R	3/8" thick	x 3/8" wide	x 10 ft. black	(9.5mm x 9.5mm x 3.04m)
DS868R	1/2" thick	x 1" wide	x 10 ft. black	(12.7mm x 25.4mm x 3.04m)

PVC Closed Cell Soft Foam A/B Tapes

DS847R	3/8" thick	x 3/8" wide	x 16.5 ft. grey	(9.5mm x 9.5mm x 5.02m)
DS848R	3/8" thick	x 3/4" wide	x 16.5 ft. grey	(9.5mm x 19mm x 5.02m)

XI Cell/Cross-Linked Polyurethane A/B Tapes

DS852R	1/8" thick	x 3/8" wide	x 16.5 ft. white	(3.2mm x 9.5mm x 5.02m)
---------------	------------	-------------	------------------	-------------------------

Camper Truck Tape-Closed Cell Sponge Vinyl A/B Tape

DS885R	3/16" thick	x 1-1/4" wide	x 30 ft. grey	(4.7mm x 32mm x 9.14m)
---------------	-------------	---------------	---------------	------------------------


Bulk Rolls

Neoprenes (Black)

DS61-50	1/8" thick	x 3/8" wide	x 50 ft. BL	(3.2mm x 9.5mm x 15.24m)
DS67-50	1/8" thick	x 1/2" wide	x 50 ft. BL	(3.2mm x 12.7mm x 15.24m)
DS74-25	5/16" thick	x 3/4" wide	x 25 ft. BL	(8mm x 19mm x 7.6m)
DS76-12.5	1/2" thick	x 3/4" wide	x 12.5 ft. BL	(12.7mm x 19.5mm x 3.8m)
DS78-50	1/4" thick	x 1" wide	x 50 ft. BL	(6.4mm x 25.4mm x 15.24m)
DS79-12.5	1/2" thick	x 1" wide	x 12.5 ft. BL	(12.7mm x 25.4mm x 3.8m)


Backer Rod

DSROD1/4	1/4" (6.3mm)	diameter	4000 ft (1219m)	per carton
DSROD3/8	3/8" (9.5 mm)	diameter	2100 ft (640m)	per carton
DSROD1/2	1/2" (12.7 mm)	diameter	2500 ft (762m)	per carton
DSROD3/4	3/4" (19mm)	diameter	1100 ft (335m)	per carton
DSROD1	1" (25.4mm)	diameter	600 ft (182m)	per carton




Sealant backer rod is an extruded round, grey, closed-cell low-density polyethylene foam with a skin-like outer texture. It is an ideal non-absorbent, compressible, back-up material inserted into a joint to control sealant tooling. Available in footage or bulk coils.


OVERHEAD VIEW



DraftSeal®



KrisTrack®



DraftSeal®

Weathersealing Specialists Since 1960

Head Office & Manufacturing Centre, Vancouver, Canada

Unit 100 - 4825 275th St, Langley, B.C. V4W 0C7 Canada

Phone: (604) 451-1080 • Fax: (604) 451-1140 • www.draftseal.com • info@draftseal.com

Outside Vancouver, B.C., please use our toll free numbers: Phone: 1-888-520-9009 Fax: 1-800-567-2887

Branch Office & Manufacturing Centre, Toronto, Canada

Phone head office toll free 1-888-520-9009 for branch address

Branch Office & Distribution Centre, Los Angeles, California, USA

Phone head office toll free 1-888-520-9009 for branch address